



AUDIOVOX®
ELECTRONICS CORP.

Rear Parking Sensor System

Model: PSB100

Users Manual



Features:

- Four reversing sensors detect obstacles up to 4.5 feet away
- Includes 0°, 4°, 8° and 16° sensor sleeves to fit most bumpers
- Activates only when vehicle is in reverse
- Will not drain battery or void factory warranty
- Includes LED/Speaker display with 3 settings - high, low, and off
- Three detection zones give the following warnings:
 - 1 = slow beep within 2.5-4.5 feet
 - 2 = medium beep within 1.3-2.5 feet
 - 3 = steady tone within 1.3 feet
- Works with any vehicle

Warnings

This product is intended to assist in safe driving by signaling the driver of obstacles behind the vehicle while the vehicle is in reverse. You, as the driver, are solely responsible for the safe operation of your vehicle and the safety of your passengers according to your local traffic regulations. Do not use any features of this system to the extent it distracts you from safe driving. Your first priority while driving should always be the safe operation of your vehicle. Audiovox Electronics Corporation cannot accept any responsibility whatsoever for accidents resulting from failure to observe these precautions or safety instructions.

1. This product utilizes high voltage. Any unauthorized modifications or damage to the product may result in electrical shock. Handle all components with care. Inspect regularly for damage to components and cabling.
2. You are responsible for ensuring that the installation of this product does not void or affect the vehicle manufacturer's warranty. Audiovox Electronics Corporation or its subsidiaries are not liable in full or in part for improper installation resulting in loss or damage to your property, or for voiding all or part of the vehicle manufacturer's warranty.
3. Do not apply excessive force to any of the components contained within this kit. Excessive force used before, during or after installation that results in a damaged or non-functional part will void all warranties.
4. Please follow the procedures in this manual. Improper installation or modification of this product will void all warranties.

Product Description

This Rear Parking Sensor System is designed to assist the driver by providing an alert when an object is behind the vehicle whenever the vehicle is shifted into reverse. Never rely solely on this product to ensure the area is clear of children and/or obstructions. This product is not intended to replace existing safety procedures, but rather to add an additional safety tool for your vehicle.

Using the Sensor System

Your backup sensing system transmits and receives ultrasonic waves from the sensors mounted in your vehicle's rear bumper. As the transmitted waves bounce off obstacles behind your vehicle and are received back by the sensors, the unit's control box converts these waves into warning sounds, or beeps, which alerts you, the driver, of obstacles behind your vehicle.

Your sensing system will signal in three increasing warning tones (beeps) which correlate the vehicle's distance from an obstacle. When the vehicle's reverse gear is engaged, the system will emit a quick beep. This indicates that the system is on and the sensors are operating. The following chart shows the detection range and beep associated with the distance of an object from the rear bumper.

Distance (feet)	Type of Beep
> 4.5ft	No beep
4.5ft – 2.5ft	Slow repeating beep
2.5ft – 1.3ft	Faster repeating beep
<1.3ft	Steady tone beep

When towing a trailer, the system will emit a solid beep. Move the switch on the speaker to the “off” position to turn off the speaker. Remember to turn the switch to the “high” or “low” position when the vehicle is no longer towing a trailer.

Specifications

Power Supply	DC9V-DC16V
Current Draw	<120mA
Detecting Distance	0ft – 4.5ft
Sensor Cable Length	19.68ft (6M)
Operating Temperature Range	-0°F ~ 176°F

Maintenance

Though your backup system requires minimum care, you should maintain its condition and performance using the following the guidelines:

- Keep the control box away from moisture, extreme heat or cold.
- Keep the sensors free from snow, ice, and debris.

Diagnostics / Trouble Shooting

Problem	Solution
No sound when reverse gear is engaged.	<ol style="list-style-type: none">1. Check if ignition/reverse light on2. Check power cable connection3. Check switch on speaker
1 Beep	System is functioning correctly
2 Beeps	1 sensor is disconnected/damaged
3 Beeps	2-3 Sensors are disconnected/damaged
4 Beeps	No sensors are connected
System beeping without obstacle behind vehicle	<ol style="list-style-type: none">1. Ensure sensor is mounted upright.2. Remove anything mounted on the vehicle that may be in the detection area.3. Ensure correct hole size has been drilled in bumper.4. Verify sensor is installed at the correct height.5. Verify sensor is in the correct position.6. Check all connections.7. Ensure module is not mounted near electrical components with high current.8. Verify supporter was used if required (angled/metal bumpers).



12 MONTH LIMITED WARRANTY

Applies to Audiovox Series Control Modules and Sensors.

AUDIOVOX Electronics Corporation (the Company) warrants to the original retail purchaser of this product that should this product or any part thereof, (other than transmitters) under normal use and conditions, be proven defective in material or workmanship within 12 months from the date of original purchase, such defect(s) will be repaired or replaced with new or reconditioned product, (at the Company's option) without charge for parts or repair labor.

To obtain repair or replacement within the terms of this Warranty, the product is to be delivered with proof of warranty coverage (e.g. dated bill of sale), specification of defect(s), transportation prepaid, to an approved warranty station. This Warranty is not assignable or transferable.

This Warranty does not cover damage to the vehicle's electrical system or costs incurred for removal or reinstallation of the product. This Warranty does not cover batteries nor apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through alteration, improper installation, mishandling, misuse, abuse, neglect, accident, or by removal or defacement of the factory serial number/bar code label(s).

This Warranty is in lieu of all other express warranties or liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHT WITHIN A PERIOD OF 24 MONTHS FROM THE DATE OF ORIGINAL PURCHASE. IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY. No person or representative is authorized to assume for the Company any liability other than expressed herein in connection with the sale of this product.

The company does not warrant that this product cannot be compromised or circumvented. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY

Audiovox Electronics Corporation, 150 Marcus Blvd., Hauppauge, New York 11788 • 1-800-645-4994

128-7075C

© 2009 Audiovox Electronics Corp., 150 Marcus Blvd., Hauppauge, N.Y. 11788



For Customer Service
Visit Our Website At
www.audiovox.com
Product Information, Photos,
FAQ's Owner's Manuals
